

| Item No.:                | WYD-LN500                                        | WYD-LN600     | WYD-LN800     | WYD-LN1000    |
|--------------------------|--------------------------------------------------|---------------|---------------|---------------|
| Input Volatge :          | 500W                                             | 600W          | 800W          | 1000W         |
| Luminous:                | 70000 lm±5%                                      | 84000 lm±5%   | 112000 lm±5%  | 140000 lm±5%  |
| Size :                   | 650*385*735mm                                    | 650*385*735mm | 742*432*790mm | 742*432*790mm |
| Weight:                  | 21.5Kg                                           | 21.5Kg        | 32.5Kg        | 32.5Kg        |
| Input Voltage :          | 100 ~ 240V AC                                    |               |               |               |
| Power Factor :           | ≥0.96                                            |               |               |               |
| Powder Efficiency:       | ≥95%                                             |               |               |               |
| CRI                      | ≥80                                              |               |               |               |
| Beam Angle:              | 15、20、30、45、60°±5 ° (Available Choice of Lenses) |               |               |               |
| Installation Method      | Pole Mounted                                     |               |               |               |
| Lighting Source          | Philips5050                                      |               |               |               |
| IP Level :               | IP65                                             |               |               |               |
| Working Temperature:     | -25 ~ +60 °C                                     |               |               |               |
| Storage Temperature:     | -30 ~ +65°C                                      |               |               |               |
| Color Temperature:       | 2700K ~ 6000K                                    |               |               |               |
| Material:                | Aluminum Alloy +Galvanized Steel                 |               |               |               |
| Light Color :            | Gray                                             |               |               |               |
| Lifetime                 | 50,000 Hrs                                       |               |               |               |
| Anti-electric shock Rate | I                                                |               |               |               |
| Dimming Control          | 0-10V /DALL/DMX512                               |               |               |               |

